



The Sullair 260 Portable Air Compressor

260 cfm at 100 psig ■ 7.4 m³/min at 7 bar

- Rotary screw compressor
- Removable modular canopy
- Adjustable height hitch
- Wheel bearing grease fittings
- Large tool box compartment
- Curbside instrument panel
- Protective shutdown switches
- SSAM – Shutdown System and Annunciation Module
- Idle warm-up valve
- Rocker type start switch
- Fuel/Water separator
- Two-stage air filters
- 0 to 100% capacity control
- Pneumatic inlet valve
- AWF Compressor Fluid
- Galvanneal sheet metal
- Durable powder coat finish
- Wide track
- Recessed tail lights
- Rear bumper



SULLAIR
Always air. Always there.™



Curbside Instrument Panel Featuring SSAM
Shutdown System & Annunciation Module.



Wheel Bearing Grease Fitting
Offers convenient wheel bearing lubrication thru zerk fittings.



Rotary Screw Design
by Sullair, the pioneer in rotary screw technology.



Sullair AWF Compressor Fluid
Improved hot and cold weather lubrication. Longer compressor fluid life. Extended air end warranty.

Designed for Total Accessibility and Reliability

Rotary Screw Compressor

Ample Service Doors

- Large service doors provide access to fuel tank, engine, compressor and tool compartment
- Service doors feature non-rusting hinges, with built-in weather strip and stainless steel T-type door retainers
- Rear service panel provides access to side by side compressor fluid cooler and engine radiator
- Serviceable components within easy reach
- Routine maintenance is simplified
- Reduced downtime and service cost

Modular Canopy and Frame

- Canopy easily removed in one piece for major service
- Modular design reduces replacement costs
- Exposed, single point lifting bail

0 to 100% Capacity Control

- Pneumatic inlet valve and unloaded starting

Highway Towable Running Gear

- 3" square drawbar
- Adjustable height hitch (14", 16", 18")
- Quick-change hitch
- Screw jack with pad
- Transport security chains
- Heavy duty leaf spring suspension
- Wide track stability

Large Curbside Tool Box

Curbside Instrument Panel

- Hinged, padlockable cover
- Mechanical air pressure gauge and hourmeter
- Rocker type engine start switch
- Idle warm-up switch

SSAM—Shutdown System & Annunciation Module

- Shutdown with annunciator light for high compressor temperature, high engine coolant temperature, low engine oil pressure and engine under-speed

Durable, Baked-on Powder Coat Finish

Two-Stage Dry Type Air Filters

- Separate filters for engine and compressor

Tier 3 Stage 3 Emissions Compliant Engines*

Air End Warranty

- 2-year standard warranty
- 5-year or 10,000-hour warranty when continuously serviced at the recommended intervals with Sullair AWF Compressor Fluid and filters

Quiet Operation

- Meets US EPA sound requirements of 76 dBA @ 7 meters

* CAT only.

Customize the compressor to meet your specific requirements with Sullair's options

Special paint
Hose reels, single and dual
Spark arrestor
Fuel level gauge
Gauge package

Tachometer
Brakes (recommended where required by law)
Mechanical parking brakes
Block heater

Ball hitch
Air filter maintenance indicators
Air filter safety elements
Low fuel shutdown

SPECIFICATIONS, WEIGHTS AND DIMENSIONS—SULLAIR 260 PORTABLE COMPRESSOR

Delivery @ Rated Pressure	Rated Pressure psig bar	Pressure Range psig bar	Designated Model	Weight ** (wet) lbs kg	Weight ** (dry) lbs kg	Length (drawbar) in mm	Length (canopy) in mm	Width in mm	Height in mm	Track Width in mm	Tire Size (load range)
260 acfm 123 l/s 7.4 m ³ /min	100 7	80–125 5.5–8.5	2-Wheel	2840 1288	2595 1177	143.3 3640	85.1 2162	65.4 1661	59.9 1522	55 1397	F 78 x 15 (C)
			Less Running Gear	2585 1173	2340 1061	—	85.1 2162	47.5 1207	49.0 1245	—	—

Engine Make	Engine Type	Engine Model	Displacement in ³ cc	Cylinders	Bore and Stroke in mm	Rated Speed rpm	Rated Power hp kW
Caterpillar	Diesel	C3.4 (Tier 3)	201 3272	4	3.70 X 4.72 94 X 120	2500	83 62
John Deere	Diesel	5030TF270 (Tier 2)	186 3028	4	3.39 X 4.13 86 X 105	2500	82 61

Capacity per CAGI/PNEUROP PN2CPTC3. (Annex D to ISO 1217)

** Weights are for John Deere. For Caterpillar, deduct 80 lbs (37 kg).



Sullair Corporation
3700 East Michigan Boulevard
Michigan City, IN 46360
Telephone: 219-879-5451
www.sullair.com

Sullair Corporation is a subsidiary of Hamilton Sundstrand Corporation, a United Technologies Company. (NYSE: UTX)
© Copyright 2011 Sullair Corporation. All rights reserved.
The color green is a registered trademark of Sullair Corporation.
Specifications subject to change without notice.
SSL-1148 1101R5



The paper used in printing this literature was manufactured using recycled fiber, either pre-consumer or post-consumer waste, therefore less harmful to the environment because less virgin fiber is used, thereby reducing tree harvesting, water usage, energy consumption, emission of greenhouse gases and pollution.

