



VT6

Designed as entry level of the VT8 model, this lighting tower maintains the same high performances and robustness. New version with Kubota Z482 engine.

- Vertical mast
- 8m max height
- Galvanized telescopic sections
- 5 adjustable stabilizers
- Certified wind stability up to 110Km/h
- Rising system with manual winch
- 4 x 1000W metal halide floodlights
- On/Off switches one for each lamp
- Low speed towing trailer, single axle
- 8 kVA 230V power generator (50/60 Hz)
- Coiled cable to supply the lamps
- Pockets and central hook for lifting the complete structure with crane or forklift
- 340° mast rotation
- 75 l fuel metal tank
- Lockable doors
- Series of alarms to prevent engine failures
- Running time of more than 60 hours
- Hour counter
- Emergency stop button
- Fuel level indicator

TECHNICAL DATA

Dimensions and weight

Min Dim. (cm) 256 x 130 x 246

Max Dim. (cm) 265 x 246 x 800

Weight (kg) 719

Illuminated area

4000 m²

Engines available

Kubota Z482, water cooled, 2 cylinders, 3000/3600 rpm

Quantity per container

20 feet: 7 units

40 feet: 14 units



VT6 4x1000W MH



VT6 4x1000W MH

VT6 LIGHT TOWER - URUGUAY



ILLUMINATED AREA: 4000 m²

